

The Borum® Master 3000 is designed with highways road marking in mind, but they also offer the perfect solution to major road marking jobs in urban areas and in less hilly areas (max driving angle is 19%). The material tank capacity for thermoplastic is 445L (118 gal.) (for the non-pressurised tank) 450L (119 gal.) (for the pressurised tank) and 440L (116 gal.) or 2x440L (2x116 gal.) for cold paint.

Data for Borum® Master 3000, basic machine:

Engine

Water-cooled, 4-cylinder Kubota Turbo Diesel engine 3600 cm³ (220 cu.in) 63kW (85 HP) @ 2600 RPM.

Compressor

Screw compressor, capacity from 1800 to 3600 L/min @ 10 bars (63,5 to 127 cfm @ 143 psi). Automatic air-flow controlling system. Integrated oil-cooling system. Air-cooler incl. water separator.

Chassis

Stable double profile frame construction. Engine, water cooler, compressor and hydraulic pumps in one unit mounted on vibration dampers.

Power steering

Dual torque steering with improved control for directional stability. Direct steering during marking and full servo assistance when manoeuvring the machine
Turning radius 4.90m (193 in).

Pointer

Stabilised against vibrations and adjustable in all directions. Easy handling, telescopic system. Fixed to frame or turning with wheels.

Transmission

Hydrostatic transmission, consisting of piston pump with variable output, controlled from the operator seat. Connected to high torque hydraulic piston motors with integrated full-torque electrohydraulic disc brakes for parking. 0-22 km/h. (0-14 mph) Manual pump for release when no engine power.
Max driving angle with weight at 6000 kg (15432 lb) 19% (11°)

Hydraulic system

Triple pump for 3 hydraulic circuits. Pumps are driven by the power take-off of the diesel engine.

Hydraulic tank

93 Litres (24,6 gal.) tank with level and temperature indicator. Hydraulic oil cooler mounted.

Fuel tank

180 Litres (48 gal.)

Pressurized bead tanks

Bead capacity 330 L (87,2 gal.)

Tank divided in two separate tanks. Individual or single outlet. Pressure max 3 bar (42,9 psi). Prepared for vakuum filling.

Operator section

Suspended two seat driver section – quick and easy slideable from left to right without the use of any tools. Steering wheel and computer panel mounted on 3D adjustable rod, which ensures perfect ergonomic positioning for the operator. For machines with spray equipment the atomizing air and tank pressure can be adjusted from the operators seat.

Gauges

Air pressure
Water temperature
Fuel level
Manometer for air pressure in glass bead tanks
Working hour counter

Electrical system

12 V/130 Amp alternator. Warning lights, rear lights, front lights, battery and relays.

Borum® LineMaster computer:

Control unit for line marking

The Borum LineMaster allows you efficient control of all road marking tasks, from line application and pre-marking to reporting and invoicing. Speed proportional control of road marking sequence when using pump solution, including material feed, material pattern and thickness.

- An 8" display which is visible in sunshine as well as in the dark
- Easy adjustment of all important parameters during marking
- Transfer of the daily marking report to an office computer via a USB stick
- Optional GPS module, allowing recording of the line marking positions
- Storage of up to 99 different line types— arranged in up to 30 marking programs
- A choice of language as per request
- Incl. foot switch

Engine bonnet

Easy access for service in left and right side.

Paint

Standard: RAL 1007.
Other colours available on request.

Viscosity

- Agglomerate: Viscosity > 8000cp
- Dots: Viscosity > 8500cp
- Extruder:
 - Viscosity lines > 6500cp
 - Viscosity rib > 8500cp

Application Methods:

Borum® Master 3000, is developed to work with one of the following application methods. Equipment to be mounted on the machine according to your specific need

Click on your choice below to see the data:

[Thermoplastic Extruder\(T\)](#)

[Thermoplastic extrusion with Dot'n Line \(DL\)](#)

[Thermoplastic Extrusion with Dot'n Line & Spray \(SP DL\)](#)

[Dot'n Line & Spray \(Pump\)\(SP P DL\)](#)

[Thermoplastic Spray with Pump \(SP/P\)](#)

[Thermoplastic Spray with Pressure Tank \(SP\)](#)

[Thermoplastic Spray with Pressure Tank and Extruder\(SP/T\)](#)

[Thermoplastic Spray with Pump and Extruder \(SP/P/T\)](#)

[Thermoplastic Extruder and Pressurized Cold Paint \(T/C\)](#)

[Pressurized Cold Paint – 1 tank or alternatively 2 tanks \(C\)](#)

[Cold Paint – Airless \(CA\)](#)

[Thermoplastic Screed box \(RL\)](#)

[2-component cold plastic \(CP\)](#)

[2-component cold plastic, Airless \(CPA\)](#)

Options:

Bead gun system

Please see data sheet on guns
[Guns and bead guns](#)

Cruise Control System

The stable marking velocity ensures a uniform quality of the road marking – layer thickness and constant pattern.

Possibility for two preset memory settings.

By a push on a button the speed is adjustable:

- 1) ± 0.1 km/h (0,063 mph) (up and down) in the interval 0-3 km/h (0-1,975 mph)
- 2) ± 0.3 km/h (0,188 mph)(up and down) in the interval 3-6 km/h (1,88 - 3,75 mph)
- 3) ± 0.5 km/h (0,31 mph)(up and down) in the interval 6-9 km/h (3,75 - 5,625 mph)



Borum International A/S
Højvangsvej 10
Hadbjerg
DK-8370 Hadsten

Phone +45 8761 3213
Fax +45 8761 3214

info@borum.as
www.borum.as



down) in the interval 6 km/h (3,75 mph) and up

Hydraulic lifting of pointer

Lifting and lowering of pointer is controlled from operator's seat.

Premark system

Electronically controlled premark system with telescopic foundation and ground distance wheel.

Cone Rack

For traffic management equipment. With or without seat.

Ejector filling of bead tank

Rack for mounting of flashing arrow

Sun roof

Hydraulic broom or air knife

For sweeping the road prior to marking; mounted just in front of the marking unit.

Modification rights reserved.



Borum International A/S
Højvangsvej 10
Hadbjerg
DK-8370 Hadsten

Phone +45 8761 3213
Fax +45 8761 3214

info@borum.as
www.borum.as



- it's straightforward

Borum Highway, 2-component cold plastic

Borum® Master 3000 CP

Borum® Master 3000 CP is a Borum Highway model with equipment for 2-component cold plastic, guns with atomizing air, agglomerate equipment, DOT equipment and extruder.

Can also be used for application of ordinary cold paint.

2-component applications includes:

- Cold spray plastic 98:2, low pressure / atomising air method
- Structured cold plastic 98:2, agglomerate, DOT application and Ribline.

Paint pressure tank – Stainless steel

440L (114 gal) pressurised tank. Max working pressure 8,5 bar (123 psi). Alternatively: 1000L (264 gal) pressurised tank, stainless steel.

Agitator

Agitator driven by hydraulic motor and with manually operated reversing valve.

Hardener tank

36L (9 gal) pressurised tank, max 8,5 bar (123 psi), stainless steel.

Cleaning system

36L (9 gal) pressure solvent tank for cleaning of mixer-head, hoses and paint guns. Stainless steel, max 8,5 bar (123 psi).

Paint filter - suction

Filter with cut-off valve for easy maintenance. For paint guns only.

Pump unit

Paint and hardener pumps are operated by one hydraulic motor for securing the right relation between paint and hardener. Capacity up to 50 L/min. (13 gal/min) The hydraulic motor is operated via a control valve governed by the line computer. The control valve automatically regulates the paint consumption according to the speed of the machine.

Retainer for paint guns

Sliding retainer frame, upon which 1 or 2 paint guns and 1 or 2 bead guns are attached. Easy slideable from side to side for an optimal working position. Ground distance is maintained by retainer wheel to ensure a constant road marking width.

Retainer lifting system

Lifting of retainer from operators seat by pneumatic cylinder.

Equipment for different application methods:

Cold spray plastic 98:2, low pressure / atomising air method

Please refer to data sheet on guns [Guns and bead guns](#)

For guns with atomising air the volume of paint applied is adjusted automatically by an electrically operated control valve according to the speed of the machine. This gives a flexible driving speed while securing the same line thickness. Static mixer is provided. If 2 guns are mounted special manifold is provided with individual cleaning of each gun.

Structured cold plastic 98:2, DOT application

The DOT head is ordered for the specific line width. The DOTs are created by pneumatic pulses, controlled from the LineMaster. The unit is provided with a static mixer.

Structured cold plastic 98:2, agglomerate application

Designed for making lines up to 400 mm wide. Each line Width has an individual application head. Under the outlet a rotating cylinder with "nails" is mounted. The rotor is hydraulically driven and the speed can be adjusted for getting the wanted pattern. The unit is provided with a static mixer.

Extruder 98:2

The extruder is ordered for the specific line width. The lines are controlled from the LineMaster. The unit is provided with a static mixer

Bead gun system

Please refer to data sheet on guns [Guns and bead guns](#)

Dimensions + weight

L: 5350 mm (210 5/8")
W: 1300 mm (51 1/4") + Equipment
H: 2250 mm (88 5/8")
incl. rotating warning light.
Weight: From 2600 up to 3800 Kg
(from 5730 up to 8380 lbs)

Options:

Sensor for measuring paint consumption

Actual paint consumption can be measured by a sensor mounted in the pump. The Line computer will then automatically show the line thickness.

Modification rights reserved.



Borum International A/S
Højvangsvej 10
Hadjbjerg
DK-8370 Hadsten

Phone +45 8761 3213
Fax +45 8761 3214

info@borum.as
www.borum.as

